

# IVYSUN

## DS6502HHD-CGS 二维高精度扫描器 2D Area Imager

高性价比  
Cost-effective



低功耗  
Low Power Consumption



- 多国语言条码信息直传
- 自感应读取条码
- 精准的红光瞄准器
- 高速、全方位的一维、二维码影像读取
- 手机屏幕条码读取
- 符合人体工程学设计

- Multiple Language Barcode Message Transfer
- Object Auto Sense
- Accurate Aimer
- Read all Mainstream 1D/2D Barcodes
- Cellphone Sscreen Barcode Reading
- Extremely Easy to Use

#### Physical Characteristics

尺寸Engine:	90mm x 67mm x 168mm
重量Weight:	120g
电压Voltage:	5VDC
电流Current:	400mA

#### Performance Characteristics

传感器像素Image(Pixels):	1280 pixels(H) x 800 pixel(V)
光源Light Source:	5600K White LED
视场角Field of View:	51°(H) x 34.5°(V)
旋转倾斜偏转Roll/Pitch/Skew:	360°, ±70°, ±70°
打印对比度Print Contrast:	≥30%
运动容差Motion Tolerances:	up to 25 in. (63.5cm) per second
接口支持Interfaces Supported:	USB, RS232 , TCP/IP网口

#### Symbology Decode Capability

一维条码/1-D	UPC, EAN, Code 128, Code 39, Code 93, Code 32 ,Code 11, Codabar, MSI, Plessey , Interleaved 2 of 5 ,Matrix 2 of 5, IATA 2 of 5, Straight 2 of 5, Codabar Interleaved 2 of 5, RSS-14, Pharmacode , Composite Code CC
二维条码/2-D	PDF417, MicroPDF417, Data Matrix, Maxicode, QR Code, MicroQR, Aztec, MaxiCode

#### User Environment

工作温度Operating Temperature:	0°C to 50°C
存储温度Storage Temperature:	-40°C to 70°C
湿度Humidity:	5% to 9% relative humidity, non-condensing
抗震动Shock Specifications	Designed to withstand 1.5m(5' ) drops
环境光免疫Ambient Light Immunity:	80,000 Lux

#### Decode Ranges

Code 39 (5 mil)	60mm-125mm
100% upca (13 mil)	35mm-310mm
1D Minimal resolution	4mil
2D Minimal resolution	9mil

Performance may be impacted by bar code quality and environmental conditions

